

Back Painted Mirror Features

- Elegant and Contemporary Finish.
- Special Lacquer with high quality.
- High resistance to moist for use in bathrooms and kitchens.
- Resistance to fading from interior UV light.
- Suitable for multiple processing such as Drilling, Grinding, Beveling, Edgeworking, Cold Screen Printing and Resin Lamination.
- Can be combined with other Glass Technologies such as Acid Etched, Titanium Coating, Digital Printing, etc.

[Contact Sales](#)



Specifications

- Available in all glass Thickness from 4mm to 12mm.
- Maximum Sheet Size: 3660x2440mm.
- Standard Size: 1830x2440mm.
- Suitable for Acid Etched processing, Titanium Coating, Golden Coating and Ice Flower.
- Available: All RAL Colors.
-

Installation Principles

- Mainly design for interior use.
- Glass Should be placed in front of an opaque wall.
- The Wall should be perfectly smooth and flat.
- On bare walls it is recommended to fix plywood panel before installing the lacquered glass.
- Not suitable for damp walls.
- Not recommended to install in areas with direct heat exposure.
- Fixing Methods:
- Adhesive: Use compatible neutral silicone or double-sided adhesive tape.
- Mechanical fixing: frames, mirror rails, mirror studs, fixing brackets or J section trims.
- The gap between two panels should normally be 1-2mm.
- The adhesive should be applied according to the manufacturer's recommendations and also allow for the circulation of air behind the lacquered glass.
- Installing on a uniformly coloured surface will give better appearance.

